



仅供参考

REV.	REVISION RECORD	DATE
A0	新图面发行	2017. 06. 16



产品型号	MODEL	ST-12
材质&电镀	MATERIAL&PLATING	
螺丝	Screw	M4. 0, 钢, 镀镍 Steel, Nickel Plated
端子	Terminal	黄铜, 1. 0t 镀锡 Brass, Tin Plated
塑件	Housing	PA66, UL94V-0
电气性能	ELECTRICAL	
额定电压	Rated voltage	300V
额定电流	Rated current	30A
绝缘电阻	Insulation resistance	500MΩ/DC500V
耐电压	Withstanding voltage	AC2000V/1min
使用线径	Wire range	22-12AWG 4. 0mm ²
机械性能	MECHANICAL	
温度范围	Temp. range	-40℃~+105℃
扭矩	Torque	1. 2N. m 10. 53Lb. in



N=Number of Contacts

	GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	深圳市思拓展电子有限公司 SHENZHEN SINTOP ELECTRONICS CO., LTD 公司网址: www.szsituo.cn 公司电话: 0755-23765350 邮 箱: 2850175982@qq.com 公司传真: 0755-23765341	PART. NO: ST-TB-0266
	LINEAR	ANGLES	APPROVED				DWG. NO:
UNIT: MM	0. 0±0. 30	X° REF±6°	DESIGNER			TITLE: Pitch11. 00mm	REV: A0
SIZE: A4	0. 000±0. 10	X° X'±2°	DRAWN	肖坤权	2017. 06. 16	American/Japanese Terminal Blocks	SHEET: 1/1